

Application note

Configuration of DA906x Control Pins

AN-PM-063

Abstract

The nSHUTDOWN and nOFF inputs (DA9063 only) and nRESETREQ (DA9061/2 only) should be correctly configured to ensure the expected device operation is achieved through a VSYS brown-out. This is achieved by selection of appropriate external pull-up supplies.

Configuration of DA906x Control Pins

Contents

Abstract	1
Contents	2
1 References	2
2 Introduction	3
3 Explanation and discussion	3
4 Recommendations	5
Revision history	6

1 References

- [1] DA9061, Datasheet, Dialog Semiconductor, 2015
- [2] DA9062, Datasheet, Dialog Semiconductor, 2015
- [3] DA9063, Datasheet, Dialog Semiconductor, 2015

Configuration of DA906x Control Pins

2 Introduction

The configuration of nSHUTDOWN and nOFF (DA9063 only) and nRESETREQ (DA9061/2 only) should be optimised to ensure correct power-up behaviour under all conditions. For these open-drain control signals it is important to choose appropriate pull-up supplies.

It should be considered that when the PMIC enters NO POWER Mode or RTC Mode, the PMIC supplies, including the 'always on' LDO1, will be turned off. This application note explains how the discharge of a pull-up rail can cause the nSHUTDOWN or nOFF inputs to be permanently-asserted, which then prevents the PMIC from leaving RESET Mode.

Note that the behaviour of the DA9063 nSHUTDOWN pin is the same as the DA9061/2 nRESETREQ pin. Please refer to the datasheets for explanations of the parameters discussed (VPOR, VDD_FAULT_LOWER and so on).

3 Explanation and discussion

The PMIC may enter NO POWER Mode or RTC Mode as a result of a VDD_FAULT condition on VSYS. (Note that there are other methods of entering RTC Mode which are not discussed here.) Examples of such fault conditions are a brown-out 'glitch' of the VSYS supply into the range $VPOR < VSYS < VDD_FAULT_LOWER$ for >100 ms, or a brown-out to $VSYS < VPOR$ of any duration. This causes an emergency shutdown of the supplies. If there is no backup battery (or it is insufficiently charged) then the VSYS fault results in the device entering NO POWER Mode. If the PMIC has RTC Mode enabled and the backup battery has sufficient charge, then the device instead enters RTC Mode.

A configuration to be avoided is illustrated in Figure 1 where nSHUTDOWN / nRESETREQ is pulled up to VLDO1. The device is shown to be stuck in RESET Mode at the right hand side of the plot. After a VSYS glitch, this same issue can be seen when the PMIC leaves either NO POWER Mode or RTC Mode. Note that the sensitivity of a particular system to the issue is dependent on the rate of rail discharge: (a) during the VSYS brown-out, and (b) after the brown-out where the PMIC regulator pull-downs are turned on. For example, Figure 1 illustrates how the discharge characteristic of VLDO3 is significantly different to VLDO1.




Figure 1: nSHUTDOWN pull-up to VLDO1 with a VSYS glitch of 20 ms down to ~0.9 V (which is below VPOR). When VSYS recovers, the PMIC attempts to leave NO POWER Mode. VDDCORE rises and, at this instant, the regulators are discharged via the PMIC internal pull-downs. The decaying LDO1 supply is seen as a logic negative-edge on nSHUTDOWN which causes the device to enter RESET Mode (indicated by a reduction of VDDCORE from 2.5 V to 2.2 V). Since nSHUTDOWN is now permanently low, the PMIC cannot exit from this state

Configuration of DA906x Control Pins

A solution to the issue which is simple and effective is to drive the nSHUTDOWN / nRESETREQ pull-up with VDDCORE (Figure 2) or VSYS (Figure 3). Similar treatment of the DA9063 nOFF pull-up is also required.

The reason the VSYS and VDDCORE supplies are unique in being unaffected by the issue, is that neither can undergo an on-to-off transition (creating falling edges on signals using them as a pull-up) when the system is powering-up or exiting RTC Mode.




Figure 2: nSHUTDOWN pull-up to VDDCORE. The PMIC correctly returns to ACTIVE Mode after a 20 ms VSYS glitch to <VPOR




Figure 3: nSHUTDOWN pull-up to VSYS. The PMIC correctly returns to ACTIVE Mode after a 20 ms VSYS glitch to <VPOR

Configuration of DA906x Control Pins

4 Recommendations

For DA9063 designs with nOFF functionality:

1. The nOFF pull-up must be supplied from either VDDCORE (via 100 k Ω) or VSYS. Alternatively, some other truly 'always-on' external supply can be used.

For DA9061/2 and DA9063 applications:

2. nSHUTDOWN / nRESETREQ should be pulled up to either VDDCORE (via 100 k Ω) or VSYS. Alternatively, some other truly 'always-on' external supply can be used.
3. nSHUTDOWN / nRESETREQ should not be pulled up to a PMIC regulator output. This is because when the line is pulled low by a system signal the device enters RESET Mode. The device is then stuck in RESET Mode since the input's pull-up rail has been turned off.
4. nSHUTDOWN / nRESETREQ should not be pulled up to the LDO1 'always on' supply. This is because this rail is turned off as the PMIC passes through NO POWER Mode (as in the event of momentary VSYS power-loss).
5. nONKEY should be pulled up to VSYS. (A pull-up to VDDCORE would create a problem with waking-up from RTC Mode.)

Level shifters might be required where the nSHUTDOWN / nRESETREQ and nOFF signals are driven from low voltage domains. For a 1.8 V domain, this can sometimes be readily implemented by including a diode-drop in the pull-up path to VDDCORE.

Configuration of DA906x Control Pins

Revision history

Revision	Date	Description
1.0	07-Sep-2015	Initial version.

Configuration of DA906x Control Pins

Status definitions

Status	Definition
DRAFT	The content of this document is under review and subject to formal approval, which may result in modifications or additions.
APPROVED or unmarked	The content of this document has been approved for publication.

Disclaimer

Information in this document is believed to be accurate and reliable. However, Dialog Semiconductor does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information. Dialog Semiconductor furthermore takes no responsibility whatsoever for the content in this document if provided by any information source outside of Dialog Semiconductor.

Dialog Semiconductor reserves the right to change without notice the information published in this document, including without limitation the specification and the design of the related semiconductor products, software and applications.

Applications, software, and semiconductor products described in this document are for illustrative purposes only. Dialog Semiconductor makes no representation or warranty that such applications, software and semiconductor products will be suitable for the specified use without further testing or modification. Unless otherwise agreed in writing, such testing or modification is the sole responsibility of the customer and Dialog Semiconductor excludes all liability in this respect.

Customer notes that nothing in this document may be construed as a license for customer to use the Dialog Semiconductor products, software and applications referred to in this document. Such license must be separately sought by customer with Dialog Semiconductor.

All use of Dialog Semiconductor products, software and applications referred to in this document are subject to Dialog Semiconductor's [Standard Terms and Conditions of Sale](#), unless otherwise stated.

© Dialog Semiconductor. All rights reserved.

RoHS Compliance

Dialog Semiconductor complies to European Directive 2001/95/EC and from 2 January 2013 onwards to European Directive 2011/65/EU concerning Restriction of Hazardous Substances (RoHS/RoHS2).

Dialog Semiconductor's statement on RoHS can be found on the customer portal <https://support.diasemi.com/>. RoHS certificates from our suppliers are available on request.

Contacting Dialog Semiconductor

United Kingdom (Headquarters)

Dialog Semiconductor PLC
Phone: +44 1793 757700

Germany

Dialog Semiconductor GmbH
Phone: +49 7021 805-0

The Netherlands

Dialog Semiconductor B.V.
Phone: +31 73 640 8822

Email:

enquiry@diasemi.com

North America

Dialog Semiconductor Inc.
Phone: +1 408 845 8500

Japan

Dialog Semiconductor K. K.
Phone: +81 3 5425 4567

Taiwan

Dialog Semiconductor Taiwan
Phone: +886 281 786 222

Web site:

www.dialog-semiconductor.com

Singapore

Dialog Semiconductor Singapore
Phone: +65 64 849929

China

Dialog Semiconductor China
Phone: +86 21 5178 2561

Korea

Dialog Semiconductor Korea
Phone: +82 2 3469 8291